



MEMOLUB®

ONE



SINGLE-POINT LUBRICATOR

REFILLABLE, DIRECT OR REMOTE INSTALLATION

4

SETTINGS



10bar



- MEMOLUB® ONE is a new refillable self-contained single-point lubricator.
- Its 10 bar ejection pressure opens up new areas of applications not possible with conventional single-point lubricators.
- Remote installation up to 2 meters from the lube point.



Reliable, simple & efficient single-point lube system

OUR OFFER

ADVANCED

Its patented pump system avoid grease separation problems. The strokes are produced at regular intervals at an ejection pressure as high as 10 bar.

SIMPLE

A unique screwing part, the Memo is used to set the lubrication program, allowing the cartridge to empty in 1, 3, 6 or 12 months. Replacing the cartridge is an easy and quick operation with no risk of changing the frequency setting and thus avoiding human errors.

VERSATILE

MEMOLUB® ONE is particularly suited for the lubrication of points that require a limited quantity of lubricant over long periods of time, such as electric motors, conveyors, fans, pumps, etc.

YOUR ADVANTAGES

ECOLOGICAL

The lubricant cartridge (made of recyclable polymer) and the battery pack are the only consumables needed to have the units work for years and years. The environmental impact is minimal. The MEMOLUB® lubricant cartridges reduce lubricant consumption, and protect your production equipment.

SAFE

MEMOLUB® ONE can be installed up to 2 m from the lube point.

Remote installation eliminates dangerous access of critical points and lubrication personnel can work safely.

ECONOMICAL

Replacing a cartridge takes less than 60 seconds! MEMOLUB® ONE ensures constant greasing, avoiding machine shutdown for lubrication tasks.

Cartridge MEMOLUB® ONE



Multi-purpose grease
for all standard application

Cartridge MEMOLUB® FOOD



Food grade grease

Specifications

Cartridge capacity :	240 cc
Dimensions :	147 x 101 mm
battery pack :	4,5V Alkaline
Min. working temperature :	-15° C
Temperature exposure range :	-25° C to +50° C
Settings :	1 - 3 - 6 or 12 month(s)
Average daily output per day :	8 - 2,6 - 1,3 or 0,65 cc
Connections :	1/4 inch R
Lubricants :	Greases up to grade NLGI 2
Max. ejection pressure :	10 bar
Warranty :	3 years

INTERNATIONALLY LEADING PRODUCTS

MEMOLUB International develops, manufactures and markets lubrication systems. The exceptional reliability and high efficiency of MEMOLUB® products have been recognised and appreciated by the industry for more than twenty years. Present in over 50 countries, we provide a reliable lubrication solution.

YOUR DISTRIBUTOR